



The robust, efficient and flexible design of the EuroCarrier makes it one of the best vessels for anchor handling, dredging support and survey activities. The EuroCarrier can be adapted to perfectly fit any project within a short time.



CLASSIFICATION	Bureau Veritas I ✕ HULL • MACH • AUT-UMS, Unrestricted Navigation, Multi-Purpose / Special Service GMDSS Area A3
DIMENSIONS	
LENGTH O.A.	34,00 meters
BREADTH MLD.	13,00 meters
DEPTH AT SIDE	4,00/4,40 meters
DRAFT	3,00 meters
GROSS TONNAGE	499
NET TONNAGE	149
PERFORMANCES	
SPEED	11 knots
BOLLARD PULL	36 tons
PROPULSION	
MAIN ENGINES	2x Caterpillar 3512
TOTAL POWER	2388 kW at 1600 RPM
THRUSTERS	2x ZF6311 1140kW 360°
AUXILIARIES	
GENERATOR SETS	2x Caterpillar C18 1x Caterpillar C6.6
TOTAL E-POWER	1020 kW
HYDRAULIC POWER PACK	4x 90 kW
BOW THRUSTER	2x ZF4010 330 kW 360°

TANKS	
FUEL OIL	220 m ³
FRESH WATER	61 m ³
DECK LAY-OUT	
ANCHOR HANDLING WINCH	190 tons holding force
PULLING FORCE	125 tons at 1 st layer
HAULING SPEED	10m/min - 20m/min
TOWING WINCH	60 tons holding force
PULLING FORCE	50 tons at 1 st layer
HAULING SPEED	10m/min - 20m/min
TUGGER WINCH	15 tons at 1 st layer
DECK CRANE FORWARD	Heila HLRM 340-2S
DECK CRANE AFT	Heila HLRM 230-3S
DECK	Azobé deck covering
TOWING HOOK	Mampaey 45 tons SWL
TOWING PINS	Aft ship: manual set, fore ship: hydraulic set + chain stopper
FENDERING	Tire- and M-fendering on the side, pushbow fendering fore- and aft ship
ACCOMMODATION	
FACILITIES	Airconditioned accommodation for up to 19 persons
OPTIONS	
DYNAMIC POSITIONING	Class 2
4-POINT MOORING SYSTEM	4 hydraulic winches and anchors
SHARK JAWS	Triplex type
CAPSTANS	5 ton, hydraulic driven

